# VELOCITY™

## INNOVATIVE & TRUSTED AUTO GLASS ADHESIVES

FIELD TESTED, OEM AND TECHNICIAN APPROVED

## FROM THE COMPANY THAT BROUGHT THE AUTO GLASS INDUSTRY THE FIRST 30 MINUTE COLD APPLIED PRODUCT.

### DEPENDABLE PRODUCTS YOU CAN COUNT ON

You can feel confident knowing you are using products that have successfully passed crash tests in all different types of conditions. In fact, our products have been "real-world" tested in more than 67 countries around the globe.

### FLEXIBILITY WHERE IT COUNTS

In-shop or mobile, SRP Velocity supplies the perfect economical and easy-to-use products to meet all your customer's needs. Trust SRP Velocity to provide you with the right products to enhance your shop's quality program and your bottom line.

SRP VELOCITY™

## FOR TECHNICIANS, BY TECHNICIANS™

SRP is part of the Fix Network, which is one of the largest automotive aftermarket services providers worldwide, with over 1,300 auto glass service corporate, franchise and affiliate units in more than 30 countries. With decades of experience in the Auto Glass Repair and Replacement (AGRR) industry, SRP Velocity brings solutions that other companies simply cannot – products designed specifically For Technicians, By Technicians.

# SRP® VELOCITY™ ADHESIVE PROPERTIES

| | VELOCITY30 | VELOCITY60 | VELOCITYPROV+ |
|---|---|---|---|
| WORKING TIME | < 15 MINUTES | < 15 MINUTES | < 20 MINUTES |
| 24 HOUR CURE THROUGH | > 3MM | > 3MM | > 3MM |
| SHORE A HARDNESS | ~ 60 | ~ 58 | ~ 60 |
| TENSILE STRENGTH (FULL CURE) | 1600PSI | 1450PSI | 1450PSI |
| TENSILE SHEAR STRENGTH (FULL CURE) | > 725PSI | > 725PSI | > 580PSI |
| UNIVERSAL MODULUS | YES | YES | YES |
| LOW CONDUCTIVE | YES | YES | YES |
| PRIMERLESS TO GLASS | NO | NO | YES |
| PACKAGING | 310ML CARTRIDGE<br>600ML FOIL | 310ML CARTRIDGE<br>600ML FOIL | 310ML CARTRIDGE<br>600ML FOIL |
| WORKING TEMPERATURE | 0°F - 140°F<br>(-17°C - 60°C) | 0°F - 140°F<br>(-17°C - 60°C) | 20°F - 120°F<br>(-6°C - 49°C) |

## VELOCITY30

- Delivers a minimum safe drive away time of 30 minutes.
- High-viscosity formula.
- Suitable for auto glass replacements requiring high modulus and/or low conductive adhesive.
- FMVSS crash test validated minimum drive away times.

## VELOCITY60

- Delivers a minimum safe drive away time of one hour.
- High-viscosity formula.
- Suitable for auto glass replacements requiring high modulus and/or low conductive adhesive.
- FMVSS crash test validated minimum drive away times.

## VELOCITYPROV+

- Primerless to glass and ceramic frit.
- High viscosity formula suitable for large windshields.
- Available in 600ml foil packs and 310ml cartridges.

## WHY CHOOSE SRP VELOCITY

SRP adhesives have been crash tested in a variety of different climatic conditions. In fact, they've been "real world" tested in more than 67 countries around the globe. Plus, you can feel confident knowing all our products have been developed and approved by professional glass technicians.Our dedicated research and development team is committed to innovation, quality and safety ensuring SRP Velocity product excellence. This commitment coupled with our history means SRP Velocity is the clear choice for shop tested and technician approved auto glass repair and replacement products.

**SRP®**
650 Pelham Blvd., Suite 100 • St. Paul, MN 55114
(800) 728-1817 • www.srpproducts.com
The SRP logo is a registered trademark of Mondofix, Inc., used under license.
VELOCITY is a trademark of Mondofix, Inc., used under license. ©2025 MONDOFIX, INC.

SRP_Literature_Urethanes_EN_20250221