INTRODUCING

VELOCITY™

INNOVATIVE AND TRUSTED URETHANES AND PRIMERS
FOR TECHNICIANS, BY TECHNICIANS™

VELOCITY PRIMERS

SIMPLIFYING THE BONDING PROCESS

VELOCITY247

- One step, blackout primer.
- Useable on glass, pinchweld, bare metal, painted surfaces, cut back urethane.
- 4-6 Minute Flash Time.
- Ensures proper chemical linking between adhesive and most surfaces.

VELOCITY CR-007

CONTAMINATION REMOVAL SYSTEM

CR-007-A

- Formulated for environmental contaminants.
- Targets fingerprints, pollen, dirt, bird droppings, tree sap, and more.
- Used with CR-007-B, prepares surface for primer application.

CR-007-B

- Formulated for industrial contaminants.
- Effectively removes grease, oil, light urethane, and more.
- Used with CR-007-A, provides a residue-free surface.

CR-007-X

- Heavy-duty paste for extreme grime removal.
- Finish with CR-007-A and CR-007-B for complete contamination elimination.

VELOCITY AUTO GLASS ADHESIVES

FIELD TESTED, OEM AND TECHNICIAN APPROVED

VELOCITY30*

- 310ml Cartridges and 600ml foilpack.
- High modulus, low conductive auto glass adhesive.

VELOCITY60*

- 310ml Cartridges and 600ml foilpack.
- High modulus, low conductive auto glass adhesive.

VELOCITYPROV+*

- Primerless to glass and ceramic frit.
- High viscosity formula suitable for large windshields.
- Available in 600ml foil packs and 310ml cartridges.

*Always refer to the SRP Velocity Drive-Away chart to determine proper minimum drive-away times.

SRP VELOCITY™

FOR TECHNICIANS, BY TECHNICIANS™

SRP is part of the Fix Network, which is one of the largest automotive aftermarket services providers worldwide, with over 1,300 auto glass service corporate, franchise and affiliate units in more than 30 countries. With decades of experience in the Auto Glass Repair and Replacement (AGRR) industry, SRP brings solutions that other companies simply cannot – products designed specifically For Technicians, By Technicians.

SRP® VELOCITY™ ADHESIVE PROPERTIES

	VELOCITY30	VELOCITY60	VELOCITYPROV+
WORKING TIME	< 15 MINUTES	< 15 MINUTES	< 20 MINUTES
24 HOUR CURE THROUGH	> 3MM	> 3MM	> 3MM
SHORE A HARDNESS	~ 60	~ 58	~ 60
TENSILE STRENGTH (FULL CURE)	1600PSI	1450PSI	1450PSI
TENSILE SHEAR STRENGTH (FULL CURE)	> 725PSI	> 725PSI	> 580PSI
UNIVERSAL MODULUS	YES	YES	YES
LOW CONDUCTIVE	YES	YES	YES
PRIMERLESS TO GLASS	NO	NO	YES
PACKAGING	310ML CARTRIDGE 600ML FOIL	310ML CARTRIDGE 600ML FOIL	310ML CARTRIDGE 600ML FOIL
WORKING TEMPERATURE	0°F - 140°F (-17°C - 60°C)	0°F - 140°F (-17°C - 60°C)	20°F - 120°F (-6°C - 49°C)

SRP® VELOCITY™ PRIMER PROPERTIES

	VELOCITY247
USE	ALL-IN-ONE BLACKOUT PRIMER
CAP COLOR	BLACK
USE WITH	ALL SRP ADHESIVES
FLASH TIME	4 TO 6 MINUTES*
ACTIVE TIME	8 HOURS
BOTTLE SIZE	100ML
OPEN SHELF LIFE	14 DAYS
IDEAL STORING TEMPERATURES**	60°F - 80°F (16°C - 27°C)
WORKING AMBIENT TEMPERATURES	40°F - 120°F (4°C - 60°C)

*Dependent on temperature. **Please see SRP Velocity Installation Manual for details.

SRP®
650 Pelham Blvd., Suite 100 • St. Paul, MN 55114
(800) 728-1817 • www.srpproducts.com
The SRP logo is a registered trademark of Mondofix, Inc., used under license.
VELOCITY is a trademark of Mondofix, Inc., used under license. ©2025 MONDOFIX, INC.

SRP_Literature_Velocity_EN_20250221