

SAFETY DATA SHEET

Prepared to U.S. OSHA, Canadian WHMIS Standards, and the Global Harmonization Standard

DATE OF PREPARATION: June 2007
DATE OF CURRENT REVISION: July 13, 2020

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY UNDERTAKING

IDENTIFICATION of the SUBSTANCE or PREPARATION:

TRADE NAME (AS LABELED):

QUICK 'N' CLEAN SCRUBS

PRODUCT CODE:

1737

RELEVANT USES of the SUBSTANCE:

Professional Hand Cleaning Towels

USES ADVISED AGAINST:

Other than Relevant Use

COMPANY/UNDERTAKING IDENTIFICATION:

U.S. DISTRIBUTOR'S NAME:

SRP

ADDRESS:

650 Pelham Boulevard, Suite 100
St Paul, MN 55114

CANADIAN DISTRIBUTOR'S NAME:

FIX AUTO

ADDRESS:

99 Émilien-Marcoux Suite 101
Blainville, Québec J7C 0B4, Canada

EMERGENCY NUMBER:

MEDICAL EMERGENCIES:

1-800-420-8036 (ProPharma) 24 hours

TRANSPORT EMERGENCIES:

1-800-424-9300 (ChemTrec) 24 hours

EMAIL ADDRESS FOR SDS INFORMATION:

msds-info@novusglass.com

2. HAZARD IDENTIFICATION

This product has been classified per GHS Standards under OSHA's Hazard Communication Standard (29CFR §1910.1200), and Canadian WHMIS (HPR). This is a self-classification.

GHS CLASSIFICATION:

Eye Irritation Category 2A

LABEL ELEMENTS:

Signal Words: Warning

Hazard Statements: H319: Causes serious eye irritation.

Precautionary Statements:

Prevention: P264: Wash thoroughly after handling. P280: Wear eye protection.

Response:

P305 + P351 + P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue Rinsing.

P337 + P313: If eye irritation persists: Get medical advice/attention.

Hazard Symbols/Pictograms: GHS07



3. COMPOSITION and INFORMATION ON INGREDIENTS

SUBSTANCE/MIXTURE:

Mixture

CHEMICAL NAME/CLASS:

Hand-Towels Saturated with Aqueous Organic Mixture

CHEMICAL NAME	CAS #	% w/w	Classification Risk Phrases/Hazard Statements
Alcohol Ethoxylates	84133-50-6	1 - 3 %	SELF CLASSIFICATION Classification: Eye Damage Cat. 1, Skin Irritation Cat. 2 Hazard Statement Codes: H318, H315 Hazard Symbols/Pictograms: GHS05
Vegetable Methyl Ester	67762-38-3	5 - 10 %	Classification: Not applicable.

4. FIRST-AID MEASURES

Contaminated individuals should be taken for medical attention if they feel unwell or if adverse effects occur. Take copy of label and SDS to physician or health professional with contaminated individual.

SKIN EXPOSURE: If skin exposure causes adverse effects, begin decontamination with running water. Recommended flushing is for 15 minutes if any sign of skin irritation develops. Contaminated individual should seek immediate medical attention if any adverse exposure symptoms develop.

EYE EXPOSURE: If direct eye contact occurs, open contaminated individual's eyes while under gently running water. Use sufficient force to open eyelids. Have contaminated individual "roll" eyes. Minimum flushing is for 15 minutes. Do not interrupt flushing. Contaminated individual must seek medical attention if any adverse effect continues after flushing.

INHALATION: If vapors from the solution are inhaled, remove contaminated individual to fresh air. If not breathing, institute cardiopulmonary resuscitation (CPR). If breathing is difficult, give oxygen. Get medical if adverse effect continues after removal to fresh air.

INGESTION: If this material is swallowed, CALL PHYSICIAN OR POISON CONTROL CENTER FOR MOST CURRENT INFORMATION. If professional advice is not available, do not induce vomiting. Victim should drink milk, egg whites, or large quantities of water. Never induce vomiting or give diluents (milk or water) to someone who is unconscious, having convulsions, or unable to swallow.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: Skin disorders may be aggravated by prolonged overexposure to this product.

RECOMMENDATIONS TO PHYSICIANS: Eliminate exposure and treat symptoms.

5. FIRE-FIGHTING MEASURES

FIRE EXTINGUISHING MATERIALS: Use extinguishing material suitable to the surrounding fire.

<u>Water Spray:</u> YES	<u>Carbon Dioxide:</u> YES
<u>Foam:</u> YES	<u>Dry Chemical:</u> YES
<u>Halon:</u> YES	<u>Other:</u> Any "ABC" Class

UNSUITABLE EXTINGUISHING MATERIALS: None known.

UNUSUAL FIRE AND EXPLOSION HAZARDS: When involved in a fire, this material may decompose and produce irritating vapors and toxic gases (e.g., oxides of nitrogen and carbon). This product must be substantially preheated for ignition to occur. Containers may build pressure and rupture in a fire.

Explosion Sensitivity to Mechanical Impact: Not applicable.

Explosion Sensitivity to Static Discharge: Not applicable.

SPECIAL FIRE-FIGHTING PROCEDURES: As with all chemical products, structural firefighters must wear Self-Contained Breathing Apparatus and full protective equipment when responding to fires involving this product. Move containers from fire area if it can be done without risk to personnel. If possible, prevent runoff water from entering storm drains, bodies of water, or other environmentally sensitive areas.

6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES:

In the event of a spill, clear the area and protect people. The atmosphere must have levels of components lower than those listed in Section 8 (Exposure Controls - Personal Protection), if applicable, and have at least 19.5 percent oxygen before personnel can be allowed into the area without Self-Contained Breathing Apparatus (SCBA).

PERSONAL PROTECTIVE EQUIPMENT: Proper protective equipment should be used.

Small Spills: Wear rubber gloves, splash goggles, and appropriate body protection.

Large Spills: Not applicable due to small size of product packaging.

ENVIRONMENTAL PRECAUTIONS:

Avoid release to the environment. Run-off water may be contaminated by other materials and should be contained to prevent possible environmental damage.

METHODS FOR CLEAN-UP AND CONTAINMENT:

Small Spills: Wear rubber gloves, splash goggles, and appropriate body protection. Wipe up spilled liquid with polypads or other suitable absorbent materials. Wash contaminated area with soap and water, absorb with paper towels, and rinse with water.

Large Spills: Not applicable due to small size of product packaging.

6. ACCIDENTAL RELEASE MEASURES, continued

METHODS FOR CLEAN-UP AND CONTAINMENT (continued):

All Spills: Floors may be slippery after spill; clean with water and suitable detergent, if necessary. Place all spill residue in a double plastic bag or other containment and seal. Decontaminate the area thoroughly. Do not mix with wastes from other materials. Dispose of in accordance with applicable U.S. Federal, State, or local procedures or appropriate standards of Canada (see Section 13, Disposal Considerations). For spills on water, contain, minimize dispersion and collect. Dispose of recovered material and report spill per regulatory requirements.

7. HANDLING and STORAGE

PRECAUTIONS FOR SAFE HANDLING: All employees who handle this material should be trained to handle it safely. Keep container tightly closed when not in use. As with all chemicals, avoid getting this product ON YOU or IN YOU. Wash thoroughly after handling this product. Do not eat, drink, smoke, or apply cosmetics while handling this product. Avoid breathing vapors or mists generated by this product. Use in a well-ventilated location. Remove contaminated clothing immediately.

CONDITIONS FOR SAFE STORAGE: Inspect all incoming containers before storage, to ensure containers are properly labelled and not damaged. Store containers in a cool, dry location, away from direct sunlight, sources of intense heat, or where freezing is possible. Empty containers may contain residual product; therefore, empty containers should be handled with care. Store containers away from incompatible chemicals (see Section 10, Stability and Reactivity).

SPECIFIC END USE(S): This product is used for cleaning hands and surfaces. Follow all industry standards for use of this product.

8. EXPOSURE CONTROLS - PERSONAL PROTECTION

EXPOSURE LIMITS:

OCCUPATIONAL/WORKPLACE EXPOSURE LIMITS/GUIDELINES:

CHEMICAL NAME	CAS #	EXPOSURE LIMITS IN AIR							OTHER
		ACGIH-TLVs		OSHA-PELs		NIOSH-RELS		NIOSH	
		TWA ppm	STEL ppm	TWA ppm	STEL ppm	TWA ppm	STEL ppm	IDLH ppm	
Alcohol Ethoxylate	84133-50-6	NE	NE	NE	NE	NE	NE	NE	NE
Vegetable Methyl Ester	67762-38-3	NE	NE	NE	NE	NE	NE	NE	NE

NE = Not Established.

CONTROL PARAMETERS:

BIOLOGICAL EXPOSURES INDICES (BEIs): Currently, there are no Biological Exposure Indices (BEIs) determined for any component of this product.

VENTILATION AND ENGINEERING CONTROLS: None normally needed under typical circumstances of use. Local exhaust may be necessary under some usage and handling situations. Prudent practice is to ensure eyewash/safety shower stations are available near areas where this product is used.

PERSONAL PROTECTIVE EQUIPMENT:

The following information on appropriate Personal Protective Equipment is provided to assist employers in complying with OSHA regulations found in 29 CFR Subpart I (beginning at 1910.132) or equivalent standards of Canada. Please reference applicable regulations and standards for relevant details.

RESPIRATORY PROTECTION: Not normally needed. If vapors are present, maintain airborne contaminant concentrations below guidelines listed in this section, if applicable. If respiratory protection is needed, use only protection authorized in 29 CFR 1910.134 or applicable State regulations. For operations in which mists or sprays of this product will be generated use only respiratory protection authorized in the U.S. Federal OSHA Respiratory Protection Standard (29 CFR 1910.134), or equivalent U.S. State standards or the Canadian CSA Standard Z94.4-93.

EYE PROTECTION: If necessary, refer to U.S. OSHA 29 CFR 1910.133 or the Canadian CSA Standard Z94.3-M1982, *Industrial Eye and Face Protectors*, for further information.

HAND PROTECTION: Wear gloves appropriate for the work being performed. If necessary, refer to U.S. OSHA 29 CFR 1910.138 and appropriate Standards of Canada for further information.

BODY PROTECTION: None normally needed under typical circumstances of use. If necessary, use body protection appropriate for task. If necessary, refer to appropriate OSHA Standards and those of Canada.

HYGIENE: See Section 7.

9. PHYSICAL and CHEMICAL PROPERTIES

The following values are for the solution:

PHYSICAL STATE: Liquid.

COLOR: Clear, colorless.

MOLECULAR FORMULA: Mixture.

MOLECULAR WEIGHT: Mixture.

ODOR: Citrus.

ODOR THRESHOLD: Not established.

pH: 6 - 8 (solution)

MELTING/FREEZING POINT: Not established.

BOILING POINT: Not established.

FLASH POINT (TCC): >93.3°C (>200°F)

EVAPORATION RATE (nBuAc = 1): Not established.

FLAMMABLE LIMITS (in air by volume, %):

Lower: Not established.

Upper: Not established.

VAPOR PRESSURE, mm Hg @ 20°C: Not established.

RELATIVE VAPOR DENSITY (air = 1): Not established.

SPECIFIC GRAVITY (water = 1): ~1.0

SOLUBILITY IN WATER: Soluble.

COEFFICIENT OF OIL/WATER DISTRIBUTION (PARTITION COEFFICIENT): Not established.

AUTOIGNITION TEMPERATURE: Not established.

VISCOSITY (cP): ~25

The following values are for the product:

APPEARANCE AND COLOR: This product is comprised of disposable hand towels in clear, colorless liquid with a citrus odor.

10. STABILITY and REACTIVITY

REACTIVITY: Product is not considered a reactivity hazard.

CHEMICAL STABILITY: Stable under typical, environmental conditions in a workplace in the absence of contaminants.

DECOMPOSITION PRODUCTS: *Combustion*: Nitrogen and carbon oxides. *Hydrolysis*: None known.

MATERIALS WITH WHICH SUBSTANCE IS INCOMPATIBLE: Strong oxidizers, strong acids, water-reactive materials.

POSSIBILITY OF HAZARDOUS REACTIONS: None known.

CONDITIONS TO AVOID: Contact with or exposure to incompatible chemicals, open flame, sparks.

11. TOXICOLOGICAL INFORMATION

INFORMATION ON TOXICOLOGICAL EFFECTS

ACUTE TOXICITY:	Not Classified.
SKIN CORROSION/IRRITATION:	Not Classified.
SERIOUS EYE DAMAGE/IRRITATION:	Eye Irritation, Category 2A.
RESPIRATORY SENSITIZATION:	Not Classified.
SKIN SENSITIZATION	Not Classified.
GERM CELL MUTAGENICITY:	Not Classified.
CARCINOGENICITY:	Not Classified.
REPRODUCTIVE TOXICITY:	Not Classified.
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE):	Not Classified.
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE):	Not Classified.

SYMPTOMS/EFFECTS AFTER INHALATION: Inhalation is not anticipated to be a significant route of exposure to this product. If vapors from the liquid portion of this product are inhaled, they may irritate the nose and other tissues of the upper respiratory system. Symptoms are generally alleviated upon breathing fresh air.

SYMPTOMS/EFFECTS AFTER CONTACT WITH SKIN or EYES: Depending on the duration and concentration of exposure, skin contact may cause irritation and reddening. Eye contact with the solution will cause irritation, redness and watering.

SYMPTOMS/EFFECTS AFTER SKIN ABSORPTION: Skin absorption is not expected to be a significant route of exposure, unless a large area of skin is involved or if contact is prolonged.

SYMPTOMS/EFFECTS AFTER INGESTION: Ingestion is not anticipated to be a likely route of exposure to this product. If this material is eaten or if ingestion occurs from contamination of the hands may cause headache, nausea, and vomiting.

12. ECOLOGICAL INFORMATION

ALL WORK PRACTICES MUST BE AIMED AT ELIMINATING ENVIRONMENTAL CONTAMINATION.

ECOTOXICITY: This product has not been tested for ecotoxicity.

PERSISTENCE AND BIODEGRADABILITY: This product has not been tested for persistence or biodegradability.

BIO-ACCUMULATION POTENTIAL: This product has not been tested for bio-accumulation potential.

MOBILITY: This product has not been tested for mobility in soil.

OTHER ADVERSE EFFECTS: Components of this product are not listed as having ozone depletion potential.

ENVIRONMENTAL EXPOSURE CONTROLS: Controls should be engineered to prevent release to the environment, including procedures to prevent spills, atmospheric release and release to waterways.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHODS: It is the responsibility of the generator to determine at the time of disposal whether the product meets the criteria of a hazardous waste per regulations of the area in which the waste is generated and/or disposed of. Waste disposal must be in accordance with all appropriate regulations. This product, if unaltered by use, may be disposed of by treatment at a permitted facility or as advised by your local hazardous waste regulatory authority. Shipment of wastes must be done with appropriately permitted and registered transporters.

DISPOSAL CONTAINERS: Empty container may be disposed of with solid waste.

PRECAUTIONS TO BE FOLLOWED DURING WASTE HANDLING: Wear proper protective equipment when handling waste materials.

U.S. EPA WASTE NUMBER: Not applicable.

14. TRANSPORTATION INFORMATION

THIS PRODUCT IS NOT HAZARDOUS AS DEFINED BY 49 CFR 172.101 BY THE U.S. DEPARTMENT OF TRANSPORTATION.

TRANSPORT CANADA TRANSPORTATION OF DANGEROUS GOODS REGULATIONS: This product is not classified as Dangerous Goods per regulations of Transport Canada.

INTERNATIONAL AIR TRANSPORT ASSOCIATION: This product is not classified as Dangerous Goods under rules of IATA.

INTERNATIONAL MARITIME ORGANIZATION (IMO): This product is not classified as Dangerous Goods under rules of the IMO.

15. REGULATORY INFORMATION

ADDITIONAL U.S. REGULATIONS:

U.S. SARA REPORTING REQUIREMENTS: The components of this product are not subject to the reporting requirements of Sections 302, 304, and 313 of Title III of the Superfund Amendments and Reauthorization Act.

U.S. SARA THRESHOLD PLANNING QUANTITY: There are no specific Threshold Planning Quantities for this product. The default Federal SDS submission and inventory requirement filing threshold of 10,000 lb (4,540 kg) may apply, per 40 CFR 370.20.

U.S. CERCLA REPORTABLE QUANTITY (RQ): Not applicable.

U.S. TSCA INVENTORY STATUS: The components of this product are listed on the TSCA Inventory.

CALIFORNIA SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT (PROPOSITION 65): No component of this product is on the California Proposition 65 lists.

ADDITIONAL CANADIAN REGULATIONS:

CANADIAN WHMIS CLASSIFICATION and SYMBOLS: see Section 2.

CANADIAN DSL INVENTORY: The components of this product are listed on the DSL Inventory.

CANADIAN ENVIRONMENTAL PROTECTION AGENCY (CEPA) PRIORITY SUBSTANCES LISTS: No component of this product is on the Priority Substances Lists.


16. OTHER INFORMATION

PREPARED BY: CHEMICAL SAFETY ASSOCIATES, Inc. • PO Box 1961, Hilo, HI 96721 (800) 969-4846
SRP CHEMISTRY DEPARTMENT • 650 Pelham Boulevard, Suite 100 • St Paul, MN 55114
(952) 944-8000

REVISION DETAILS:



July 2012: Prepare GHS SDS.
August 2016: Review, rearrange information in Sections 2, 5, 8, 9, 11, and 15 of SDS.
August 2017: Review and update to particulars of Canada's HPR adopting the Globally Harmonized System. Update Toxicological data (in Section 11). Update Canadian distributor, formatting.
July 2020: New company name.

NFPA RATING



Hazard Scale: 0 = Minimal 1 = Slight
2 = Moderate 3 = Serious 4 = Severe

FOR SOLUTION SATURATING TOWELS

HAZARDOUS MATERIAL IDENTIFICATION SYSTEM			
HEALTH HAZARD (BLUE)	1*		
FLAMMABILITY HAZARD (RED)	1		
PHYSICAL HAZARD (YELLOW)	0		
PROTECTIVE EQUIPMENT			
EYES	RESPIRATORY	HANDS	BODY
	SEE SECTION 8		SEE SECTION 8
For Routine Industrial Use and Handling Applications			

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate
3 = Serious 4 = Severe * = Chronic hazard

DEFINITIONS OF TERMS

A large number of abbreviations and acronyms appear on a SDS. Some of these which are commonly used include the following:

CAS #: This is the Chemical Abstract Service Number that uniquely identifies each constituent.

EXPOSURE LIMITS IN AIR:

CEILING LEVEL: The concentration that shall not be exceeded during any part of the working exposure.

DFG MAK Germ Cell Mutagen Categories: **1:** Germ cell mutagens which have been shown to increase the mutant frequency in the progeny of exposed humans. **2:** Germ cell mutagens which have been shown to increase the mutant frequency in the progeny of exposed mammals. **3A:** Substances which have been shown to induce genetic damage in germ cells of human or animals, or which produce mutagenic effects in somatic cells of mammals *in vivo* and have been shown to reach the germ cells in an active form. **3B:** Substances which are suspected of being germ cell mutagens because of their genotoxic effects in mammalian somatic cell *in vivo*; in exceptional cases, substances for which there are no *in vivo* data, but which are clearly mutagenic *in vitro* and structurally related to known *in vivo* mutagens. **4:** Not applicable (Category 4 carcinogenic substances are those with non-genotoxic mechanisms of action. By definition, germ cell mutagens are genotoxic. Therefore, a Category 4 for germ cell mutagens cannot apply. At some time in the future, it is conceivable that a Category 4 could be established for genotoxic substances with primary targets other than DNA [e.g. purely aneugenic substances] if research results make this seem sensible.) **5:** Germ cell mutagens, the potency of which is considered to be so low that, provided the MAK value is observed, their contribution to genetic risk for humans is expected not to be significant.

DFG MAK Pregnancy Risk Group Classification: **Group A:** A risk of damage to the developing embryo or fetus has been unequivocally demonstrated. Exposure of pregnant women can lead to damage of the developing organism, even when MAK and BAT (Biological Tolerance Value for Working Materials) values are observed. **Group B:** Currently available information indicates a risk of damage to the developing embryo or fetus must be considered to be probable. Damage to the developing organism cannot be excluded when pregnant women are exposed, even when MAK and BAT values are observed. **Group C:** There is no reason to fear a risk of damage to the developing embryo or fetus when MAK and BAT values are observed. **Group D:** Classification in one of the groups A-C is not yet possible because, although the data available may indicate a trend, they are not sufficient for final evaluation.

IDLH-Immediately Dangerous to Life and Health: This level represents a concentration from which one can escape within 30-minutes without suffering escape-preventing or permanent injury.

LOQ: Limit of Quantitation.

SKIN: Used when there is a danger of cutaneous absorption.

STEL-Short Term Exposure Limit: Short Term Exposure Limit, usually a 15-minute time-weighted average (TWA) exposure that should not be exceeded at any time during a workday, even if the 8-hr TWA is within the TLV-TWA, PEL-TWA or REL-TWA.

TLV-Threshold Limit Value: An airborne concentration of a substance that represents conditions under which it is generally believed that nearly all workers may be repeatedly exposed without adverse effect. The duration must be considered, including the 8-hour.

TWA-Time Weighted Average: Time Weighted Average exposure concentration for a conventional 8-hr (TLV, PEL) or up to a 10-hr (REL) workday and a 40-hr workweek.

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM HAZARD

RATINGS: This rating system was developed by the National Paint and Coating Association and has been adopted by industry to identify the degree of chemical hazards.

HEALTH HAZARD:

0 (Minimal Hazard): No significant health risk, irritation of skin or eyes not anticipated. *Skin Irritation:* Essentially non-irritating. PII or Draize = "0". *Eye Irritation:* Essentially non-irritating, or minimal effects which clear in < 24 hours [e.g. mechanical irritation]. Draize = "0". *Oral Toxicity LD₅₀ Rat:* < 5000 mg/kg. *Dermal Toxicity LD₅₀Rat or Rabbit:* < 2000 mg/kg. *Inhalation Toxicity 4-hrs LC₅₀ Rat:* < 20 mg/L.; **1 (Slight Hazard):** Minor reversible injury may occur; slightly or mildly irritating. *Skin Irritation:* Slightly or mildly irritating. *Eye Irritation:* Slightly or mildly irritating. *Oral Toxicity LD₅₀ Rat:* > 500-5000 mg/kg. *Dermal Toxicity LD₅₀Rat or Rabbit:* > 1000-2000 mg/kg. *Inhalation Toxicity LC₅₀ 4-hrs Rat:* > 2-20 mg/L.; **2 (Moderate Hazard):** Temporary or transitory injury may occur. *Skin Irritation:* Moderately irritating; primary irritant; sensitizer. PII or Draize > 0, < 5. *Eye Irritation:* Moderately to severely irritating and/or corrosive; reversible corneal opacity; corneal involvement or irritation clearing in 8-21 days. Draize > 0, ≤ 25. *Oral Toxicity LD₅₀ Rat:* > 50-500 mg/kg. *Dermal Toxicity LD₅₀Rat or Rabbit:* > 200-1000 mg/kg. *Inhalation Toxicity LC₅₀ 4-hrs Rat:* > 0.5-2 mg/L.; **3 (Serious Hazard):** Major injury likely unless prompt action is taken and medical treatment is given; high level of toxicity; corrosive. *Skin Irritation:* Severely irritating and/or corrosive; may destroy dermal tissue, cause skin burns, dermal necrosis. PII or Draize > 5-8 with destruction of tissue. *Eye Irritation:* Corrosive, irreversible destruction of ocular tissue; corneal involvement or irritation persisting for more than 21 days. Draize > 80 with effects irreversible in 21 days. *Oral Toxicity LD₅₀ Rat:* > 1-50 mg/kg. *Dermal Toxicity LD₅₀Rat or Rabbit:* > 20-200 mg/kg. *Inhalation Toxicity LC₅₀ 4-hrs Rat:* > 0.05-0.5 mg/L.; **4 (Severe Hazard):** Life-threatening; major or permanent damage may result from single or repeated exposure. *Skin Irritation:* Not appropriate. Do not rate as a "4", based on skin irritation alone. *Eye Irritation:* Not appropriate. Do not rate as a "4", based on eye irritation alone. *Oral Toxicity LD₅₀ Rat:* ≤ 1 mg/kg. *Dermal Toxicity LD₅₀Rat or Rabbit:* ≤ 20 mg/kg. *Inhalation Toxicity LC₅₀ 4-hrs Rat:* ≤ 0.05 mg/L).

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM HAZARD RATINGS (continued):

FLAMMABILITY HAZARD:

0 (Minimal Hazard-Materials) that will not burn in air when exposure to a temperature of 815.5°C [1500°F] for a period of 5 minutes.; **1 (Slight Hazard-Materials)** that must be pre-heated before ignition can occur. Material require considerable pre-heating, under all ambient temperature conditions before ignition and combustion can occur, including: Materials that will burn in air when exposed to a temperature of 815.5°C (1500°F) for a period of 5 minutes or less; Liquids, solids and semisolids having a flash point at or above 93.3°C [200°F] (e.g. OSHA Class IIIB, or; Most ordinary combustible materials [e.g. wood, paper, etc.]; **2 (Moderate Hazard-Materials)** that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur. Materials in this degree would not, under normal conditions, form hazardous atmospheres in air, but under high ambient temperatures or moderate heating may release vapor in sufficient quantities to produce hazardous atmospheres in air, including: Liquids having a flash-point at or above 37.8°C [100°F] Solid materials in the form of course dusts that may burn rapidly but that generally do not form explosive atmospheres; Solid materials in a fibrous or shredded form that may burn rapidly and create flash fire hazards (e.g. cotton, sisal, hemp; Solids and semisolids that readily give off flammable vapors.); **3 (Serious Hazard-Liquids and solids)** that can be ignited under almost all ambient temperature conditions. Materials in this degree produce hazardous atmospheres with air under almost all ambient temperatures, or, unaffected by ambient temperature, are readily ignited under almost all conditions, including: Liquids having a flash point below 22.8°C [73°F] and having a boiling point at or above 38°C [100°F] and below 37.8°C [100°F] [e.g. OSHA Class IB and IC]; Materials that on account of their physical form or environmental conditions can form explosive mixtures with air and are readily dispersed in air [e.g., dusts of combustible solids, mists or droplets of flammable liquids]; Materials that burn extremely rapidly, usually by reason of self-contained oxygen [e.g. dry nitrocellulose and many organic peroxides]; **4 (Severe Hazard-Materials)** that will rapidly or completely vaporize at atmospheric pressure and normal ambient temperature or that are readily dispersed in air, and which will burn readily, including: Flammable gases; Flammable cryogenic materials; Any liquid or gaseous material that is liquid while under pressure and has a flash point below 22.8°C [73°F] and a boiling point below 37.8°C [100°F] [e.g. OSHA Class IA; Material that ignite spontaneously when exposed to air at a temperature of 54.4°C [130°F] or below [e.g. pyrophoric].

PHYSICAL HAZARD:

0 (Water Reactivity): Materials that do not react with water. *Organic Peroxides:* Materials that are normally stable, even under fire conditions and will not react with water. *Explosives:* Substances that are Non-Explosive. *Unstable Compressed Gases:* No Rating. *Pyrophorics:* No Rating. *Oxidizers:* No "0" rating allowed. *Unstable Reactives:* Substances that will not polymerize, decompose, condense or self-react.; **1 (Water Reactivity):** Materials that change or decompose upon exposure to moisture. *Organic Peroxides:* Materials that are normally stable, but can become unstable at high temperatures and pressures. These materials may react with water, but will not release energy. *Explosives:* Division 1.5 & 1.6 substances that are very insensitive explosives or that do not have a mass explosion hazard. *Compressed Gases:* Pressure below OSHA definition. *Pyrophorics:* No Rating. *Oxidizers:* Packaging Group III; *Solids:* any material that in either concentration tested, exhibits a mean burning time less than or equal to the mean burning time of a 3:7 potassium bromate/cellulose mixture and the criteria for Packing Group I and II are not met. *Liquids:* any material that exhibits a mean pressure rise time less than or equal to the pressure rise time of a 1:1 nitric acid (65%)/cellulose mixture and the criteria for Packing Group I and II are not met. *Unstable Reactives:* Substances that may decompose, condense or self-react, but only under conditions of high temperature and/or pressure and have little or no potential to cause significant heat generation or explosive hazard. Substances that readily undergo hazardous polymerization in the absence of inhibitors.; **2 (Water Reactivity):** Materials that may react violently with water. *Organic Peroxides:* Materials that, in themselves, are normally unstable and will readily undergo violent chemical change, but will not detonate. These materials may also react violently with water. *Explosives:* Division 1.4 – Explosive substances where the explosive effect are largely confined to the package and no projection of fragments of appreciable size or range are expected. An external fire must not cause virtually instantaneous explosion of almost the entire contents of the package. *Compressed Gases:* Pressurized and meet OSHA definition but < 514.7 psi absolute at 21.1°C (70°F) [500 psig]. *Pyrophorics:* No Rating. *Oxidizers:* Packing Group II *Solids:* any material that, either in concentration tested, exhibits a mean burning time of less than or equal to the mean burning time of a 2:3 potassium bromate/cellulose mixture and the criteria for Packing Group I are not met. *Liquids:* any material that exhibits a mean pressure rise time less than or equal to the pressure rise of a 1:1 aqueous sodium chlorate solution (40%)/cellulose mixture and the criteria for Packing Group I are not met. *Unstable Reactives:* Substances that may polymerize, decompose, condense, or self-react at ambient temperature and/or pressure, but have a low potential for significant heat generation or explosion. Substances that readily form peroxides upon exposure to air or oxygen at room temperature);

DEFINITIONS OF TERMS (Continued)

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM HAZARD RATINGS (continued):

3 (Water Reactivity): Materials that may form explosive reactions with water. *Organic Peroxides:* Materials that are capable of detonation or explosive reaction, but require a strong initiating source, or must be heated under confinement before initiation; or materials that react explosively with water. *Explosives:* Division 1.2 – Explosive substances that have a fire hazard and either a minor blast hazard or a minor projection hazard or both, but do not have a mass explosion hazard. *Compressed Gases:* Pressure ≥ 514.7 psi absolute at 21.1°C (70°F) [500 psig]. *Pyrophorics:* No Rating. *Oxidizers:* Packing Group I *Solids:* any material that, in either concentration tested, exhibits a mean burning time less than the mean burning time of a 3:2 potassium bromate/cellulose mixture. *Liquids:* Any material that spontaneously ignites when mixed with cellulose in a 1:1 ratio, or which exhibits a mean pressure rise time less than the pressure rise time of a 1:1 perchloric acid (50%) cellulosic mixture. *Unstable Reactives:* Substances that may polymerize, decompose, condense or self-react at ambient temperature and/or pressure and have a moderate potential to cause significant heat generation or explosion.; **4 (Water Reactivity):** Materials that react explosively with water without requiring heat or confinement. *Organic Peroxides:* Materials that are readily capable of detonation or explosive decomposition at normal temperature and pressures. *Explosives:* Division 1.1 & 1.2-explosive substances that have a mass explosion hazard or have a projection hazard. A mass explosion is one that affects almost the entire load instantaneously. *Compressed Gases:* No Rating. *Pyrophorics:* Add to the definition of Flammability “4”. *Oxidizers:* No “4” rating. *Unstable Reactives:* Substances that may polymerize, decompose, condense or self-react at ambient temperature and/or pressure and have a high potential to cause significant heat generation or explosion.).

NATIONAL FIRE PROTECTION ASSOCIATION HAZARD RATINGS:

HEALTH HAZARD: 0 (materials that, under emergency conditions, would offer no hazard beyond that of ordinary combustible materials): Gases and vapors whose LC₅₀ for acute inhalation toxicity is greater than 10,000 ppm. Dusts and mists whose LC₅₀ for acute inhalation toxicity is greater than 200 mg/L. Materials whose LD₅₀ for acute dermal toxicity is greater than 2000 mg/kg. Materials whose LD₅₀ for acute oral toxicity is greater than 2000 mg/kg. Materials that are essentially non-irritating to the respiratory tract, eyes and skin. **1** (materials that, under emergency conditions, can cause significant irritation): Gases and vapors whose LC₅₀ for acute inhalation toxicity is greater than 5,000 ppm but less than or equal to 10,000 ppm. Dusts and mists whose LC₅₀ for acute inhalation toxicity is greater than 10 mg/L but less than or equal to 200 mg/L. Materials whose LD₅₀ for acute dermal toxicity is greater than 1000 mg/kg but less than or equal to 2000 mg/kg. Materials whose LD₅₀ for acute oral toxicity is greater than 500 mg/kg but less than or equal to 2000 mg/kg. Materials that cause slight to moderate irritation to the respiratory tract, eyes and skin. **2** (materials that, under emergency conditions, can cause temporary incapacitation or residual injury): Gases and vapors whose LC₅₀ for acute inhalation toxicity is greater than 3,000 ppm but less than or equal to 5,000 ppm. Dusts and mists whose LC₅₀ for acute inhalation toxicity is greater than 2 mg/L but less than or equal to 10 mg/L. Materials whose LD₅₀ for acute dermal toxicity is greater than 200 mg/kg but less than or equal to 1000 mg/kg. Materials whose LD₅₀ for acute oral toxicity is greater than 50 mg/kg but less than or equal to 500 mg/kg. Any liquid whose saturated vapor concentration at 20°C (68°F) is equal to or greater than one-fifth its LC₅₀ for acute inhalation toxicity, if its LC₅₀ is less than or equal to 5000 ppm and that does not meet the criteria for either degree of hazard 3 or degree of hazard 4. Compressed liquefied gases with boiling points between -30°C (-22°F) and -55°C (-66.5°F) that cause severe tissue damage, depending on duration of exposure. Materials that are respiratory irritants. Materials that cause severe, but reversible irritation to the eyes or are lachrymators. Materials that are primary skin irritants or sensitizers. **3** (materials that, under emergency conditions, can cause serious or permanent injury): Gases and vapors whose LC₅₀ for acute inhalation toxicity is greater than 1,000 ppm but less than or equal to 3,000 ppm. Dusts and mists whose LC₅₀ for acute inhalation toxicity is greater than 0.5 mg/L but less than or equal to 2 mg/L. Materials whose LD₅₀ for acute dermal toxicity is greater than 40 mg/kg but less than or equal to 200 mg/kg. Materials whose LD₅₀ for acute oral toxicity is greater than 5 mg/kg but less than or equal to 50 mg/kg. Any liquid whose saturated vapor concentration at 20°C (68°F) is equal to or greater than one-fifth its LC₅₀ for acute inhalation toxicity, if its LC₅₀ is less than or equal to 3000 ppm and that does not meet the criteria for degree of hazard 4. Compressed liquefied gases with boiling points between -30°C (-22°F) and -55°C (-66.5°F) that cause frostbite and irreversible tissue damage. Materials that are respiratory irritants. Cryogenic gases that cause frostbite and irreversible tissue damage. Materials that are corrosive to the respiratory tract. Materials that are corrosive to the eyes or cause irreversible corneal opacity. Materials that are corrosive to the skin. **4** (materials that, under emergency conditions, can be lethal): Gases and vapors whose LC₅₀ for acute inhalation toxicity is less than or equal to 1,000 ppm. Dusts and mists whose LC₅₀ for acute inhalation toxicity is less than or equal to 0.5 mg/L. Materials whose LD₅₀ for acute dermal toxicity is less than or equal to 40 mg/kg. Materials whose LD₅₀ for acute oral toxicity is less than or equal to 5 mg/kg. Any liquid whose saturated vapor concentration at 20°C (68°F) is equal to or greater than one-fifth its LC₅₀ for acute inhalation toxicity, if its LC₅₀ is less than or equal to 1000 ppm.

NATIONAL FIRE PROTECTION ASSOCIATION HAZARD RATINGS (continued):

FLAMMABILITY HAZARD: 0 Materials that will not burn under typical fire conditions, including intrinsically noncombustible materials such as concrete, stone, and sand: Materials that will not burn in air when exposed to a temperature of 816°C (1500°F) for a period of 5 minutes in accordance with Annex D. **1** Materials that must be preheated before ignition can occur. Materials in this degree require considerable preheating, under all ambient temperature conditions, before ignition and combustion can occur: Materials that will burn in air when exposed to a temperature of 816°C (1500°F) for a period of 5 minutes in accordance with Annex D. Liquids, solids and semisolids having a flash point at or above 93.4°C (200°F) (i.e. Class IIIB liquids). Liquids with a flash point greater than 35°C (95°F) that do not sustain combustion when tested using the Method of Testing for Sustained Combustibility, per 49 CFR 173, Appendix H or the UN Recommendation on the Transport of Dangerous Goods, Model Regulations (current edition) and the related Manual of Tests and Criteria (current edition). Liquids with a flash point greater than 35°C (95°F) in a water-miscible solution or dispersion with a water non-combustible liquid/solid content of more than 85 percent by weight. Liquids that have no fire point when tested by ASTM D 92 Standard Test Method for Flash and Fire Points by Cleveland Open Cup, up to a boiling point of the liquid or up to a temperature at which the sample being tested shows an obvious physical change. Combustible pellets with a representative diameter of greater than 2 mm (10 mesh). Solids containing greater than 0.5 percent by weight of a flammable or combustible solvent are rated by the closed up flash point of the solvent. Most ordinary combustible materials. **2** Materials that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur. Materials in this degree would not under normal conditions form hazardous atmospheres with air, but under high ambient temperatures or under moderate heating could release vapor in sufficient quantities to produce hazardous atmospheres with air: Liquids having a flash point at or above 37.8°C (100°F) and below 93.4°C (200°F) (i.e. Class II and Class IIIA liquids.) Solid materials in the form of powders or coarse dusts of representative diameter between 420 microns (40 mesh) and 2 mm (10 mesh) that burn rapidly but that generally do not form explosive mixtures in air. Solid materials in fibrous or shredded form that burn rapidly and create flash fire hazards, such as cotton, sisal and hemp. Solids and semisolids that readily give off flammable vapors. Solids containing greater than 0.5 percent by weight of a flammable or combustible solvent are rated by the closed cup flash point of the solvent. **3** Liquids and solids that can be ignited under almost all ambient temperature conditions. Materials in this degree produce hazardous atmospheres with air under almost all ambient temperatures or, though unaffected by ambient temperatures, are readily ignited under almost all conditions: Liquids having a flash point below 22.8°C (73°F) and having a boiling point at or above 37.8°C (100°F) and those liquids having a flash point at or above 22.8°C (73°F) and below 37.8°C (73°F) and below 37.8°C (100°F) (i.e. Class IB and IC liquids). Materials that, on account of their physical form or environmental conditions, can form explosive mixtures with air and are readily dispersed in air. Flammable or combustible dusts with a representative diameter less than 420 microns (40 mesh). Materials that burn with extreme rapidity, usually by reason of self-contained oxygen (e.g. dry nitrocellulose and many organic peroxides). Solids containing greater than 0.5 percent by weight of a flammable or combustible solvent are rated by the closed cup flash point of the solvent. **4** Materials that will rapidly or completely vaporize at atmospheric pressure and normal ambient temperature or that are readily dispersed in air and will burn readily: Flammable gases. Flammable cryogenic materials. Any liquid or gaseous materials that is liquid while under pressure and has a flash point below 22.8°C (73°F) and a boiling point below 37.8°C (100°F) (i.e. Class IA liquids). Materials that ignite when exposed to air, Solids containing greater than 0.5 percent by weight of a flammable or combustible solvent are rated by the closed cup flash point of the solvent.

INSTABILITY HAZARD: 0 Materials that in themselves are normally stable, even under fire conditions: Materials that have an estimated instantaneous power density (product of heat of reaction and reaction rate) at 250°C (482°F) below 0.01 W/mL. Materials that do not exhibit an exotherm at temperatures less than or equal to 500°C (932°F) when tested by differential scanning calorimetry. **1** Materials that in themselves are normally stable, but that can become unstable at elevated temperatures and pressures: Materials that have an estimated instantaneous power density (product of heat of reaction and reaction rate) at 250°C (482°F) at or above 0.01 W/mL and below 10 W/mL. **2** Materials that readily undergo violent chemical change at elevated temperatures and pressures: Materials that have an estimated instantaneous power density (product of heat of reaction and reaction rate) at 250°C (482°F) at or above 10 W/mL and below 100W/mL. **3** Materials that in themselves are capable of detonation or explosive decomposition or explosive reaction, but that require a strong initiating source or that must be heated under confinement before initiation: Materials that have an estimated instantaneous power density (product of heat of reaction and reaction rate) at 250°C (482°F) at or above 100 W/mL and below 1000 W/mL. Materials that are sensitive to thermal or mechanical shock at elevated temperatures and pressures. **4** Materials that in themselves are readily capable of detonation or explosive decomposition or explosive reaction at normal temperatures and pressures: Materials that have an estimated instantaneous power density (product of heat of reaction and reaction rate) at 250°C (482°F) of 1000 W/mL or greater. Materials that are sensitive to localized thermal or mechanical shock at normal temperatures and pressures.

DEFINITIONS OF TERMS (Continued)

FLAMMABILITY LIMITS IN AIR:

Much of the information related to fire and explosion is derived from the National Fire Protection Association (NFPA). **Flash Point** - Minimum temperature at which a liquid gives off sufficient vapors to form an ignitable mixture with air. **Autoignition Temperature**: The minimum temperature required to initiate combustion in air with no other source of ignition. **LEL** - the lowest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source. **UEL** - the highest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source.

TOXICOLOGICAL INFORMATION:

Human and Animal Toxicology: Possible health hazards as derived from human data, animal studies, or from the results of studies with similar compounds are presented. Definitions of some terms used in this section are: **LD₅₀** - Lethal Dose (solids & liquids) which kills 50% of the exposed animals; **LC₅₀** - Lethal Concentration (gases) which kills 50% of the exposed animals; **ppm** concentration expressed in parts of material per million parts of air or water; **mg/m³** concentration expressed in weight of substance per volume of air; **mg/kg** quantity of material, by weight, administered to a test subject, based on their body weight in kg. Other measures of toxicity include **TDLo**, the lowest dose to cause a symptom and **TCLo** the lowest concentration to cause a symptom; **TDo**, **LDLo**, and **LDo**, or **TC**, **TCo**, **LCLo**, and **LCo**, the lowest dose (or concentration) to cause lethal or toxic effects. **Cancer Information:** The sources are: **IARC** - the International Agency for Research on Cancer; **NTP** - the National Toxicology Program, **RTECS** - the Registry of Toxic Effects of Chemical Substances, **OSHA** and **CAL/OSHA**. IARC and NTP rate chemicals on a scale of decreasing potential to cause human cancer with rankings from 1 to 4. Subrankings (2A, 2B, etc.) are also used. **Other Information:** **BEI** - ACGIH Biological Exposure Indices, represent the levels of determinants which are most likely to be observed in specimens collected from a

healthy worker who has been exposed to chemicals to the same extent as a worker with inhalation exposure to the TLV.

ECOLOGICAL INFORMATION:

EC is the effect concentration in water. **BCF** = Bioconcentration Factor, which is used to determine if a substance will concentrate in lifeforms which consume contaminated plant or animal matter. **TL_m** = median threshold limit; Coefficient of Oil/Water Distribution is represented by **log K_{ow}** or **log K_{oc}** and is used to assess a substance's behavior in the environment.

REGULATORY INFORMATION:

U.S. and CANADA:

ACGIH: American Conference of Governmental Industrial Hygienists, a professional association which establishes exposure limits.

This section explains the impact of various laws and regulations on the material. **EPA** is the U.S. Environmental Protection Agency. **NIOSH** is the National Institute of Occupational Safety and Health, which is the research arm of the U.S. Occupational Safety and Health Administration (**OSHA**). **WHMIS** is the Canadian Workplace Hazardous Materials Information System. **DOT** and **TC** are the U.S. Department of Transportation and the Transport Canada, respectively. Superfund Amendments and Reauthorization Act (**SARA**); the Canadian Domestic/Non-Domestic Substances List (**DSL/NDL**); the U.S. Toxic Substance Control Act (**TSCA**); Marine Pollutant status according to the **DOT**; the Comprehensive Environmental Response, Compensation, and Liability Act (**CERCLA** or **Superfund**); and various state regulations. This section also includes information on the precautionary warnings which appear on the material's package label. **OSHA** - U.S. Occupational Safety and Health Administration. **EC**, European Economic Community).